



TECHNICAL PRODUCT INFORMATION

- Product: Stabilized Clear Mulch
- Catalog Number: E1102
- Product description: Stabilized clear mulch film. The film is transparent to incoming radiation and traps the longer wavelengths re-radiating from the soil, Having the greatest warming potential comparing to black and colored mulch. The film decreases the soil water loss and can be used for solarization.
- Durability: 1 Season at 120 Kly
- Thickness: 25 μ
- Width: According to customer order
- Length: According to customer order

Property	Test Method	Units	Value
Tensile Strength at break [MD]	ASTM D-882	MPa.	20
Tensile Strength at break [TD]	ASTM D-882	MPa.	20
Elongation at break [MD]	ASTM D-882	%	500
Elongation at break [TD]	ASTM D-882	%	500
Falling Dart Impact	ASTM D-1709	gr.	130
Total light transmission	Internal	%	90
Thickness average	Israeli Stnd. 821	%	±8% on nominal
Thickness tolerance	Israeli Stnd. 821	%	±15%



Kibbutz Einat P.O.B 3 | Einat 4880500 Israel | Tel :+972-3-9016060 | Fax:+972-3-9016040

All statements, information and data given herein are believed to be accurate a reliable, but are presented without guaranty, warranty or responsibility any kind, express or limited. Statement or suggestion concerning possible use of our products are made without representation or warranty that any such use is free of patent infringement, and are not recommendation to infringe any patent. The user should not assume that all safety measures are indicated, or that other measures may not be required