



**Diffused thermic  
Stabilized film  
with anti-fog**

## TECHNICAL PRODUCT INFORMATION

Product:	Stabilized thin Mulch
Catalog Number:	E1105
Product description:	Stabilized very thin clear mulch film. The film increases the soil temp. and decreases the soil water loss. To be used for early vegetables
UV Resistance:	1 Season at 120-130Kly
Thickness:	15 $\mu$
Width:	Up to 4.0 m
Length:	According to customer order

Property	Test Method	Units	Value
Tensile Strength at break [MD]	ASTM D-882	MPa.	30
Tensile Strength at break [TD]	ASTM D-882	MPa.	30
Elongation at break [MD]	ASTM D-882	MPa.	300
Elongation at break [TD]	ASTM D-882	MPa.	600
Falling Dart Impact	ASTM D-1709	gr.	100
Total light transmission	EN-2155	%	90
Thickness average	EN 13206	%	±8% on nominal
Thickness tolerance	EN 13206	%	±15%



**Kibbutz Einat P.O.B 3 | Einat 4880500 Israel | Tel :+972-3-9016060 | Fax:+972-3-9016040**

All statements, information and data given herein are believed to be accurate a reliable, but are presented without guaranty, warranty or responsibility any kind, express or limited. Statement or suggestion concerning possible use of our products are made without representation or warranty that any such use is free of patent infringement, and are not recommendation to infringe any patent. The user should not assume that all safety measures are indicated, or that other measures may not be required