



## **TECHNICAL PRODUCT INFORMATION**

40 µ

Product: Stabilized film for solarization+AF

Catalog Number: E1320

Product description: Clear Stabilized film for solarization. The plastic sheets allow the sun's radiant energy to be trapped in the soil and heating the soil. Solarization during the hot summer months can increase soil temperature to levels that kill many diseases and weed seed. Soil solarization also improves soil structure and increases the availability of nitrogen (N) and other essential plant nutrients. Solarization is a simple, safe, and effective method that has been used with field, vegetable, and flower crops. It can be combined with organic soil amendments or reduced rates of pesticide application for greater effectiveness.

Thickness: UV Resistance:

12 months (3–6 months exposed to direct sunlight and 6–9 months under greenhouse)

Property	Test Method	Units	Value	
Tensile Strength at break [MD]	ASTM D-882	MPa.	18	
Tensile Strength at break [TD]	ASTM D-882	MPa.	18	MULCH
Elongation at break [MD]	ASTM D-882	%	250	
Elongation at break [TD]	ASTM D-882	%	350	
Falling Dart Impact	ASTM D-1709	gr.	150	ANTI FOG
Total light transmission	EN 2155	%	90	ANTI DRIP
Thickness average	EN13206	%	±5 on nominal	
Thickness tolerance	EN13206	%	±15% on each point	

## Kibbutz Einat P.O.B 3 | Einat 4880500 Israel | Tel :+972-3-9016060 | Fax:+972-3-9016040

All statements, information and data given herein are believed to be accurate a reliable, but are presented without guaranty, warranty or responsibility any kind, express or limited. Statement or suggestion concerning possible use of our products are made without representation or warranty that any such use is free of patent infringement, and are not recommendation to infringe any patent. The user should not assume that all safety measures are indicated, or that other measures may not be required