



## TECHNICAL PRODUCT INFORMATION

Product:	Stabilized film+ Anti-fog
Catalog Number:	E1413
Product description:	Clear stabilized PE film with high mechanical properties for low tunnels.
UV Resistance:	1 Seasons
Thickness:	80-100 $\mu$
Width:	0.5-2.5 m
Length:	According to customer order

Property	Test Method	Units	Value
Tensile Strength at break [MD]	ASTM D-882	MPa.	25
Tensile Strength at break [TD]	ASTM D-882	MPa.	25
Elongation at break [MD]	ASTM D-882	%	500
Elongation at break [TD]	ASTM D-882	%	500
Falling Dart Impact	ASTM D-1709	gr.	600
Total light transmission	UV-VIS	%	88 min
Thermicity	FTIR		65-70
Thickness average	Israeli Stnd. 821	%	$\pm 5\%$ on nominal
Thickness tolerance	Israeli Stnd. 821	%	$\pm 15\%$



**Kibbutz Einat P.O.B 3 | Einat 4880500 Israel | Tel :+972-3-9016060 | Fax:+972-3-9016040**

All statements, information and data given herein are believed to be accurate a reliable, but are presented without guaranty, warranty or responsibility any kind, express or limited. Statement or suggestion concerning possible use of our products are made without representation or warranty that any such use is free of patent infringement, and are not recommendation to infringe any patent. The user should not assume that all safety measures are indicated, or that other measures may not be required