




Diffused thermic film with anti-fog for tunnels

TECHNICAL PRODUCT INFORMATION

- Product: Diffused thermic film with anti-fog for tunnels
- Catalog Number: E1601
- Product description: Multi-layer PE film. The anti-fog additives to prevent dripping onto the plants and IR ingredient reduce heat "escape" at night.
- UV Resistance: 1-2 Seasons
- Thickness: 100-120 μ
- Width: 1.0-14.5 m
- Length: According to customer order

Property	Test Method	Units	Value
Tensile Strength at break [MD]	ASTM D-882	MPa.	18
Tensile Strength at break [TD]	ASTM D-882	MPa.	18
Elongation at break [MD]	ASTM D-882	MPa.	500
Elongation at break [TD]	ASTM D-882	MPa.	500
Tear resistance [MD]	ASTM D-1922	Kg./mm	7.0
Tear resistance [TD]	ASTM D-1922	Kg./mm	10
Falling Dart Impact	ASTM D-1709	gr.	800
Total light transmission	Internal	%	90
Light diffusion	Internal	%	50
Thermicity	Internal (FTIR)	%	80
UV blocking	Internal	%/nm	NA
Thickness average	Israeli Stnd. 821	%	$\pm 5\%$ on nominal
Thickness tolerance	Israeli Stnd. 821	%	$\pm 15\%$



Kibbutz Einat P.O.B 3 | Einat 4880500 Israel | Tel :+972-3-9016060 | Fax:+972-3-9016040

All statements, information and data given herein are believed to be accurate a reliable, but are presented without guaranty, warranty or responsibility any kind, express or limited. Statement or suggestion concerning possible use of our products are made without representation or warranty that any such use is free of patent infringement, and are not recommendation to infringe any patent. The user should not assume that all safety measures are indicated, or that other measures may not be required